G1.5X3WH6-A





Choose from 36 sizes of PANDUIT® Type G Wiring Duct from 0.5 "x 0.5" up to 6" x 4" in popular
colors. Used for general purpose control panel wiring and to route and protect wiring in
communication closets. The non-slip cover conceals all wiring and is easy to install. The duct
and cover form a flush sidewall providing increased capacity and improved aesthetics.

Specifications

- Made of lead-free PVC
- UL Recognized continuous use temperature: 122 °F (50°C)
- UL94 Flammability Rating of V-0
- Conforms with NFPA 79-2002 section 14.3.1 requirement for flame retardant material
- Provided with mounting holes

Features and Benefits

- Wide finger/slot design provides greater sidewall rigidity and can be used with a wide range of wire bundle sizes
- PANDUIT® exclusive rounded edges protects hands and wiring/cabling from abrasion
- Non-slip cover stays in place during shipment, vibration and when in vertical orientation, eliminating rework
- Flush cover design holds 10-12% more wires than traditional duct designs
- Double scoreline allows quick modification for larger cabling bundles saving installation time leading to a lower installed cost
- Specially formulated lead-free material eliminates health concerns associated with PVC that contains lead
- Restricted slot design retains wire in slot for fast, easy wire installation or removal
- Base and cover sold separately.

| ■ Part Number | G1.5X3WH6-A |
|--|---------------------------------------|
| ■ RoHS Compliancy Status | Compliant |
| ■ Part Description | Wide finger, slotted wiring duct. |
| ■ Material | Lead-Free PVC |
| ■ Color | White |
| ■ CSA Certified | Yes |
| ■ UL Recognized (File No. E147128) | Yes |
| ■ Length (ft.) | 6 |
| Adhesive Mounting Tape | Yes |
| CE Marking | Yes |
| ■ Duct Size W x H (In.) | 1.75 x 3.12 |
| ■ Duct Size W x H (mm) | 44.5 x 79.2 |
| ■ Mounting Method | Standard Mounting Holes with Adhesive |
| ■ Pricing Description | Slotted Duct, PVC,1.5"X3"X6',ADH,WHT |

| ■ Slot Width (In.) | 0.31 |
|----------------------------------|---------|
| ■ Slot Width (mm) | 7.9 |
| ■ Cover Part Number | C1.5WH6 |
| Min. Order UOM | FT |
| ■ Min. Order Qty. | 6 |

■ BOM Qty. (# of Pkgs.)

