

HLS5S-X0



- Strip Ties (HLS) - Rolls performed in convenient 6", 12" and 18" strips
- 15' & 75' Rolls (HLM/HLS-15 & 75) - Can be cut to desired length, eliminating waste
- Adjustable, releasable, and reusable hundreds of times – ideal for applications requiring frequent moves, adds, or changes
- Hook and loop material maintains network data integrity by protecting against over-tensioning of high performance copper and fiber cables
- Easy to use and operator safe with no sharp edges
- Complementary mounts available

Note: Minimum 2" overlap required to achieve loop tensile rating

▪ Part Number	HLS5S-X0
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Hook & Loop Cable Tie, Strips, 18.0", Standard cross section
▪ Product Type	Cable Ties
▪ Material	Nylon Loop, Polyethylene Hook
▪ Color	Black
▪ CSA Certified	No
▪ UL Listed (File #E56854)	No
▪ UL Recognized (File #E56854)	No
▪ Length (In.)	18.0
▪ Length (mm)	457
▪ Width (In.)	.750
▪ Width (mm)	19.1
▪ CE Compliant	Yes
▪ Cross Section	Standard
▪ Locking Style	Hook & Loop
▪ Max. Bundle Diameter (In.)	5.00
▪ Max. Bundle Diameter (mm)	127
▪ Min. Bundle Diameter (In.)	.25
▪ Min. Bundle Diameter (mm)	6
▪ Min. Loop Tensile Strength (Lbs.)	50
▪ Min. Loop Tensile Strength (N)	222
▪ Pricing Description	Hook & Loop Tie, Strip, Black 18.0"L (457mm), .75"W (19.1mm), Black
▪ Temperature Range	0°F to 220°F
▪ Thickness (In.)	.10
▪ Thickness (mm)	2.5

▪ Min. Order UOM	PC
▪ Min. Order Qty.	10
▪ BOM Qty. (# of Pkgs.)	

