

Current refinements (click  to remove)

[Search Tips](#) 
 [Region](#) **USA**  [Product Family](#) **Flex Conductor, Two-Hole, Standard Barrel with Window Lug**  [Text Search:](#) 'LCDX6-10A-L'

**Your search criteria matched only one product, shown below.**

For Use with Flexible, Extra-Flexible, and Code Stranded Copper Conductors

- Can be used with code conductor and flex conductor class: G, H, I, K, M and Diesel Locomotive
- Generously beveled wire entry prevents bent back strands when inserting conductor into barrel
- Color-coded barrels marked with *PANDUIT* and specified competitor die index numbers for proper crimp die selection
- Inspection window to visually assure full conductor insertion
- Tin-plated to inhibit corrosion
- UL Listed and CSA Certified to 35 KV\*\* and temperature rated to 90°C when crimped with *PANDUIT* and specified competitor crimping tools and dies
- American Bureau of Shipping Approved
- Available with NEMA hole sizes and spacing


**Related Products**

- [Contour Crimp™ Control...](#)
- [Die Type, Battery Powered Hydraulic...](#)
- [Die Type, Battery Powered Hydraulic...](#)
- [CD-2001 Crimping Dies](#)
- [Die Type, Manual Hydraulic, 14 Ton,...](#)
- [Die Type, Remote Hydraulic, 14 Ton,...](#)
- [More...](#)



Part Number:	LCDX6-10A-L
RoHS Compliancy Status:	Compliant
Part Description:	Flex Lug, #6 AWG, 2-hole, #10 Stud Holes, .63 Hole Spacing
CSA Certified:	Yes
UL Listed:	Yes
Length (In.):	1.82
Length (mm):	46.2
Class G,H, I, K, M:	#6 AWG
Diesel Locomotive:	#6 AWG
Stud Hole Size (In.):	#10
Stud Hole Spacing (In.):	.63
Tongue Width (In.):	.46
Barrel Length (In.):	.48
Angle:	Straight
Figure No.:	1
Panduit Color Code:	Blue
Panduit Die Index No.:	P24
Tongue Thickness:	.08
Tongue Type:	Standard
Tongue Width (mm):	11.7
Wire Strip Length (In.):	9/16
Min. Order UOM:	PC
Min. Order Qty.:	1
Burndy Die Index No.:	7
T&B Die Index No.:	24

BOM Qty. (# of Pkgs.)

[Add to My Catalog](#)

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	6 STR/FLEX
Wire Type	Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive
Wire Strip Length	9/16 in.
Stud Size	#10
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLUE
Panduit Die Index No. on Barrel	P24
Alternate Industry Die Index No. ( ) on Barrel	(7)



00	6/03	SAC	SAC	RELEASED	10850
REV	DATE	BY	CHK	DESCRIPTION	ECN

**PANDUIT CORP. TINLEY PARK, ILLINOIS**

LCDX6-10A-L  
Copper Lug - Two-Hole, Standard Flex Barrel

SCALE N/A DRAWING NO / CAD FILE LCDX6-10A-CUST