

MRS6S-C4



• • 360° radial seal eliminates gaps under the head of the tie to provide a completely sealed installation

• Self-locking cable tie design locks into place at any length along the tie body, unlike fixed diameter band clamps

- Available in AISI 304 stainless steel for general-purpose applications
- Available in AISI 316 stainless steel for the most corrosive environments

Part Number	MRS6S-C4
 RoHS Compliancy Status 	Compliant
 Part Description 	360° radial seal retained tension, stainless steel cable tie, standard, 6.0" (152mm) max. bundle diameter
 Product Type 	Cable Ties
 Material 	Stainless Steel Type 304
Length (In.)	23.8
 Length (mm) 	604
 Width (In.) 	.18
Width (mm)	4.4
 Cross Section 	Standard
Max. Bundle Diameter (In.)	6.0
Max. Bundle Diameter (mm)	152
 Min. Bundle Diameter (In.) 	.75
 Min. Bundle Diameter (mm) 	19.1
 Min. Loop Tensile Strength (Lbs. 	.) 180
Min. Loop Tensile Strength (N)	800
 Pricing Description 	Radial Seal Tie, 304 SS, Standard, 23.8" (604mm), .010" (.25mm) thk
Thickness (In.)	.010
 Thickness (mm) 	.25
Tool	MTRTLS
Min. Order UOM	PC
Min. Order Qty.	100
POM Oty (# of Dkgo)	

BOM Qty. (# of Pkgs.)

PANDUIT Part no.	PACKAGE QTY.	MAX,BUNDLE DIAMETER	LENGTH "L" ±.3" [7]
MRSIS-C4	100	1"[25]	8.1" [205]
MRS2S-C4	100	2" [5]]	11.3" [287]
MRS4S-C4	100	4" [102]	17.6" [447]
MRS6S-C4	100	6" [152]	23.8" [604]

