MRT1S-C4





- Provide tight bundling of armored cables, pipes, conduit and other rigid materials in harsh conditions for a reliable, easy to install fastening solution
 - Self-locking cable tie design locks into place at any length along the tie body, unlike fixed diameter band clamps
 - Smooth surfaces and rounded edges assures cable protection and worker safety
 - Available in AISI 304 stainless steel for general-purpose applications
 - Available in AISI 316 stainless steel for the most corrosive environments

	Mark to the second of the seco		
Part Number	MRT1S-C4		
 RoHS Compliancy Status 	Compliant		
■ Part Description	Retained tension, s	stai	nless steel cab
Product Type	Cable Ties		
Material	Stainless Steel Typ	e 3	304
■ Length (In.)	8.1		
Length (mm)	205		
Width (In.)	.18		
■ Width (mm)	4.4		
 Cross Section 	Standard		
Max. Bundle Diameter (In.)	1.0		
■ Max. Bundle Diameter (mm)	25		
Min. Bundle Diameter (In.)	.75		
■ Min. Bundle Diameter (mm)	19.1		
 Min. Loop Tensile Strength (Lbs.) 180		
 Min. Loop Tensile Strength (N) 800		
■ Pricing Description	Retained Tension T	Γie,	304 SS, Stand
■ Thickness (In.)	.010		
■ Thickness (mm)	.25		
■ Tool	MTRTLS		
Min. Order UOM	PC		
Min. Order Qty.	100		
■ BOM Qty. (# of Pkgs.)			

