THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PANDUIT WE I GHT COVER REMOVED FOR CLARITY PART NO. BREAKOUT AREA 1.2 LB/10 PCS POST FOR TAMPER (3 PLACES) PAN-TY LOOP FOR NK4BX\*\*-AY (530.0 g/10 PCS) RESISTANT SCREW CABLE HOLD-DOWN NOTES: (4 PLACES) 1. SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND OR PACKAGE QUANTITY. 2. SEE CATALOG FOR A COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH (0)THIS PART. 3. DIMENSIONS IN PARENTHESES ARE IN METRIC. 4. ALSO INCLUDED WITH BOX:  $\tilde{O}_{l}$ **1**0 1 - BOX BASE 3.28 1 - BOX COVER 2- PLT1.51-C PAN-TY [83.3] O PANDUIT 0 2- MOUNTING SCREW (L) (E) 1- MOUNTING SCREW (USED TO 1 🕳 2 3 **=** 4 **=** SECURE COVER TO BASE) LABEL/LABEL COVER 2- STRIP OF 1.25" X .75" FOAM TAPE FOR MOUNTING 5. BREAKOUTS DESIGNED TO ACCEPT LD3/LDP3 OR LD5/LDP5 RACEWAY. 6. BASE MATERIAL THICKNESS: .090[2.29]. MOUNTING HOLES FOR #6 PAN HEAD **⊲** 1.23 → SCREW (2 PLACES) [31.2] NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WITH RESPECT TO ADHESIVE BOND PERFORMANCE. AMONG OTHER THINGS, THE CONDITIONS UNDER WHICH THESE MOUNTS MAY BE APPLIED AND/OR THE SURFACE TO WHICH THEY MAY BE APPLIED ARE BEYOND PANDUIT'S CONTROL. 3.26 SIZE [82.8] DRAWING FILENAME M02479BB\_DC028\_00A.PRT NETKEY 4 POSITION SURFACE MOUNT BOX CUSTOMER DRAWING I.I. NUMBER N/A CORP PRODUCT SPEC N/A TINLEY PARK, IL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. WORK INSTRUCTION N/A DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 NONE THIRD ANGLE PROJECTION (.XX) ±.01 ANGLES ± 1° DRAWN BY MATERIAL: PART NO. JsP NK4BX\*\*-AY 5-2-07 JsP 5-2-07 RELEASED TO PRODUCTION 02479-028 DRAWING NO. ABS CHK 'D 02479-028 REV DATE BY CHK DESCRIPTION ECN - R CUST SUP