



Current refinements (click  to remove)

[Search Tips](#) 
 [Region](#)  [USA](#)
 [Product Family](#)  [Ring Terminal, Large Wire Non-Insulated](#)
 [Text Search: 'P8-10R-Q'](#)
Your search criteria matched only one product, shown below.


- Designed for use with #8 - #2 AWG copper wire
- Ring tongue design assures a secure connection in high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Brazed seam protects terminal barrel from splitting during the crimp process
- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Maximum recommended operating temperature 302°F (150°C)

‡UL and CSA approved tooling/product combinations.

Part Number:	P8-10R-Q
RoHS Compliancy Status:	Compliant
Part Description:	Ring terminal, large wire, 8 AWG, #10 stud size, non-insulated.
Product Type:	Terminals
CSA Certified:	Yes
UL Listed:	Yes
Length (In.):	1.14
Width (In.):	.47
Angle:	straight
Clearance:	.43
Stock:	.04
Stud Size:	#10
Tool:	CT-1701‡
Wire Range:	8 AWG
Wire Range (mm ²):	10
Min. Order UOM:	PC
Min. Order Qty.:	25

BOM Qty. (# of Pkgs.)

[Add to My Catalog](#)

 Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

