



PLT1M-C



- For indoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- A variety of materials and colors available for specific applications
- Miniature to Standard cross sections feature a curved tip for easy threading and handling

| | |
|-------------------------------------|------------------------------------------|
| ■ Part Number | PLT1M-C |
| ■ RoHS Compliancy Status | Compliant |
| ■ Part Description | Cable Tie, 3.9", Miniature cross section |
| ■ Product Type | Cable Ties |
| ■ Material | Nylon 6.6 |
| ■ Color | Natural |
| ■ CSA Certified | Yes |
| ■ Mil. Std. Part Number | MS3367-4-9 |
| ■ UL Listed (File #E56854) | Yes |
| ■ UL Recognized (File #E56854) | Yes |
| ■ Length (In.) | 3.9 |
| ■ Length (mm) | 99 |
| ■ Width (In.) | .098 |
| ■ Width (mm) | 2.5 |
| ■ CE Compliant | Yes |
| ■ Cross Section | Miniature |
| ■ Head Height (In.) | .154 |
| ■ Head Height (mm) | 3.9 |
| ■ Head Width (In.) | .180 |
| ■ Head Width (mm) | 4.6 |
| ■ Locking Style | Locking |
| ■ Material Flammability Rating | UL 94V-2 |
| ■ Max. Bundle Diameter (In.) | .87 |
| ■ Max. Bundle Diameter (mm) | 22 |
| ■ Max. Continuous Use Temperature | 185°F (85°C) |
| ■ Min. Loop Tensile Strength (Lbs.) | 18 |

| | |
|----------------------------------|----------------------------------------------------|
| ■ Min. Loop Tensile Strength (N) | 80 |
| ■ Pricing Description | Cable Tie, 3.9"L (99mm), Miniature, Nylon, Natural |
| ■ Thickness (In.) | .043 |
| ■ Thickness (mm) | 1.1 |
| ■ Tool | GTS, GTSL, GS2B, PTS, PPTS, STS2 |
| ■ Min. Order UOM | PC |
| ■ Min. Order Qty. | 100 |
| ■ BOM Qty. (# of Pkgs.) | |

