



PLT8H-L



- For indoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- A variety of materials and colors available for specific applications
- Miniature to Standard cross sections feature a curved tip for easy threading and handling

■ Part Number	PLT8H-L
■ RoHS Compliancy Status	Compliant
■ Part Description	Cable Tie, 30.6", Heavy cross section
■ Product Type	Cable Ties
■ Material	Nylon 6.6
■ Color	Natural
■ CSA Certified	Yes
■ UL Listed (File #E56854)	No, however does meet the requirements of UL181B-C, for use with UL non-metallic air ducts and air connectors
■ UL Recognized (File #E56854)	Yes
■ Length (In.)	30.6
■ Length (mm)	779
■ Width (In.)	.350
■ Width (mm)	8.9
■ CE Compliant	Yes
■ Cross Section	Heavy
■ Head Height (In.)	.340
■ Head Height (mm)	8.6
■ Head Width (In.)	.560
■ Head Width (mm)	14.2
■ Locking Style	Locking
■ Material Flammability Rating	UL 94V-2
■ Max. Bundle Diameter (In.)	9.00
■ Max. Bundle Diameter (mm)	229
■ Max. Continuous Use Temperature	185°F (85°C)
■ Min. Loop Tensile Strength (Lbs.)	175
■ Min. Loop Tensile Strength (N)	778

■ Pricing Description	Cable Tie, 30.6"L (779mm), Heavy, Nylon, Natural
■ Thickness (In.)	.078
■ Thickness (mm)	2.0
■ Tool	GTH, GS4H, GS4EH, PTH, STH2, ST3EH
■ Min. Order UOM	PC
■ Min. Order Qty.	50
■ BOM Qty. (# of Pkgs.)	

