



## PRT10EH-Q0



- Greater resistance to damage caused by ultraviolet light – indoor or outdoor use
- Release tab permits easy release and re-use where changes are anticipated during development, production or servicing in the field
- Typically used for heavy duty applications such as securing conduit or large cable bundles to permanent structures
- Strongest *Pan-Ty*® Cable Tie available
- Can be used with mounting clip (MCEH-S25-C0)

■ Part Number	PRT10EH-Q0
■ RoHS Compliancy Status	Compliant
■ Part Description	Cable Tie, Releasable, 34.2", Extra-Heavy cross section
■ Product Type	Cable Ties
■ Material	Weather Resistant Nylon 6.6
■ Color	Black
■ CSA Certified	No
■ UL Listed (File #E56854)	No
■ UL Recognized (File #E56854)	No
■ Length (In.)	34.2
■ Length (mm)	869
■ Width (In.)	.500
■ Width (mm)	12.7
■ CE Compliant	Yes
■ Cross Section	Extra-Heavy
■ Head Height (In.)	.400
■ Head Height (mm)	10.2
■ Head Width (In.)	.800
■ Head Width (mm)	20.3
■ Locking Style	Releasable
■ Material Flammability Rating	UL 94-HB
■ Max. Bundle Diameter (In.)	10.00
■ Max. Bundle Diameter (mm)	254
■ Max. Continuous Use Temperature	185°F (85°C)
■ Min. Loop Tensile Strength (Lbs.)	250
■ Min. Loop Tensile Strength (N)	1112

■ Pricing Description	Cable Tie, Releasable, 34.2"L (869mm), Extra-Heavy, Weather Resistant, Black
■ Thickness (In.)	.085
■ Thickness (mm)	2.2
■ Tool	Hand install only
■ Min. Order UOM	PC
■ Min. Order Qty.	25
■ BOM Qty. (# of Pkgs.)	

