



SE50PFR-CR0



- Provides continuous abrasion resistance for wires cables and tubing
- Lightweight durable protection
- Highly flexible open weave will not trap heat or humidity
- Rated for use up to 257°F (125°C)
- Allows for use with irregular shapes
- Self extinguishing meets UL VW-1
- Stock colors: Black or gray with white tracer or in white with black tracer to identify flame retardant materials.

• Part Number	SE50PFR-CR0
• RoHS Compliancy Status	Compliant
• Part Description	Flame Retardant Braided Expandable Sleeving provides continuous abrasion resistance for wires, cables and tubing. The highly flexible open weave will not trap heat or humidity.
• Material	Flame Retardant Polyethylene Terephthalate
• Color	Black
• CSA Certified	Yes
• UL Recognized	E116868
• Length (m)	30.5
• Flammability Rating	UL224 VW-1
• Inside Diameter (mm)	12.7
• Length Per Reel (ft.)	100
• Length Per Reel (m)	30.5
• Nominal Diameter Range (In.)	.250 to .750
• Nominal Diameter Range (mm)	6.4 to 19.1
• Nominal I.D. (In.)	.50
• Nominal I.D. (mm)	12.7
• Pricing Description	Exp. Sleeving, .50" (12.7mm), Flame Ret., Black
• Temperature Range	-94°F to 257°F (-70°C to 125°C)
• Min. Order UOM	RL
• Min. Order Qty.	1
• BOM Qty. (# of Pkgs.)	