



SE75PSC-CR0



▪ Part Number	SE75PSC-CR0
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Fray Resistant Braided Expandable Sleeving resists fraying when cut with scissors and provides continuous abrasion resistance for wires, cables and tubing. The highly flexible open weave will not trap heat or humidity.
▪ Material	Polyethylene Terephthalate
▪ Color	Black
▪ CSA Certified	Yes
▪ UL Recognized	E116868
▪ Bundle Diameter Range	.63 to 1.0
(In.)	
▪ Bundle Diameter Range	15.9 to 25.4
(mm)	
▪ Flammability Rating	UL94 HB
▪ Inside Diameter (mm)	19.1
▪ Length Per Reel (ft.)	100
▪ Length Per Reel (m)	30.5
▪ Nominal Diameter	.63 to 1.0
Range (In.)	
▪ Nominal Diameter	15.9 to 25.4
Range (mm)	
▪ Nominal I.D. (In.)	.75
▪ Nominal I.D. (mm)	19.1
▪ Pricing Description	Exp. Sleeving, .75" (19.1mm),Black
▪ Temperature Range	-94°F to 257°F (-70°C to 125°C)
▪ Min. Order UOM	RL
▪ Min. Order Qty.	1