



## T25F-C



- Largest variety of colors materials and sizes in the industry
- Available in seven different materials and twelve different colors
- Colors conform to Communications Wiring Standards
- Flexible, neat, fast
- Allows breakouts of single/multiple wires and rerouting of replacement wires
- Harness multiple cables into a single manageable bundle
- A protection for wires cables hoses and tubing
- Color code wire bundles
- Reusable
- Tool supplied in each package
- \*Order number of reels required.
- \*\*Flame retardant products are manufactured from a material that is rated UL94V-0.
- ‡Reel packaging may contain splices.

• Part Number	T25F-C
• RoHS Compliancy Status	Compliant
• Part Description	Spiral Wrap offers abrasion protection for wires, cables, hoses and tubing
• Material	Polyethylene
• Color	Natural
• UL Recognized	E141152
• Length (ft.)	100
• Length (m)	30.5
• Bundle Diameter Range (In.)	3/16 to 2
• Bundle Diameter Range (mm)	4.8 to 50.4
• Flammability Rating	UL94 HB
• Length Per Reel (ft.)	100
• Length Per Reel (m)	30.5
• Min. Bundle Diameter (In.)	3/16
• Min. Bundle Diameter (mm)	4.8
• Outside Diameter (In.)	.25
• Outside Diameter (mm)	6.4
• Pricing Description	Spiral Wrap, .25" (6.3mm) x 100', Poly, Natural
• Temperature Range	-40°F to 122°F (-40°C to 50°C)
• Wall Thickness (In.)	.04
• Wall Thickness (mm)	1.02
• Wrap Width (In.)	.375
• Wrap Width (mm)	9.5

• Min. Order UOM RL

• Min. Order Qty. 1

• BOM Qty. (# of Pkgs.)