



T400X000Y2T



- Used to mark egress routes, fire alarms, and fire equipment that is clearly visible for up to ten hours after power is lost
- Absorb energy from ambient light and releases this energy in the form of a glow when power is lost
- Can be used in the *PANDUIT* thermal transfer desktop printers to create direction arrow tape, striped tape, or safety signs on demand
- *PANDUIT* Photoluminescent Tapes meet or exceed the following safety standard specification for photoluminescent safety markings including: ASTM E 2072-00, ASTM E 2073-00, ASTM E 2030-99, DIN67510-1, IMO Resolution A.752.18, ISO/CD 15370, DIN 67510, UL 924, ASTM 162, ASTM 648, ASTM 662, MIL-L-3891 B, NFPA 101 Life Safety Code, OSHA 1910.137

■ Part Number	T400X000Y2T
■ RoHS Compliancy Status	Compliant
■ Part Description	Photoluminescent, polyester tape.
■ Height (In.)	4.00
■ Height (mm)	101.60
■ Length (ft.)	15.0
■ Length (m)	4.5
■ Width (In.)	4.00
■ Width (mm)	101.60
■ Legend	Blank
■ Pricing Description	ThermTrans, Continuous Tape, Photoluminescent Polyester, 4.00" W x 15' L, Green, 3 inch core
■ Min. Order UOM	RL
■ Min. Order Qty.	1
■ BOM Qty. (# of Pkgs.)	