TMEH-S8-C0







- Mounts designed specially for use with *PANDUIT* Extra-Heavy cross section ties for mounting cable, large wire bundles or tubular shapes.
- Unique cradle design provides maximum stability for cable bundle
 - Route and support large diameter and heavy cable bundles
- ‡ Cable Tie Cross Section Sizes: M = Miniature, I = Intermediate, S = Standard, HS = Heavy-Standard, LH = Light-Heavy, H = Heavy, HLM = Miniature *Tak-Ty*® Hook & Loop Cable Ties.

	Part Number	TMEH-S8-C0
	RoHS Compliancy Status	Compliant
	Part Description	Extra Heavy Cable Tie Mount
	Material	Weather Resistant Nylon 6.6
	Color	Black
-	UL Recognized	E136577
•	Height (In.)	.61
	Height (mm)	15.5
	Length (In.)	1.62
	Length (mm)	41.1
	Width (In.)	.72
	Width (mm)	18.3
	Environment	Outdoors
	Flammability Rating	UL94 V-2
•	Hole Diameter (In.)	.18
-	Hole Diameter (mm)	4.3
	Max. Bundle Diameter (mm)	12.7
	Mounting Method	#8 (M4) Screw
	Pricing Description	Cable Tie Mount, Extra-Heavy, #8 Screw (M4), Weather Resistant Nylon
	Screw Size	#8 (M4)
	Screw Size Metric	M4
	Used With Cable Ties	I, S, H, EH
	Min. Order UOM	PC
-	Min. Order Qty.	100
	BOM Qty. (# of Pkgs.)	

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




PANDUIT PART NUMBER*	*MATERIAL SUFFIX	'A'	'В'	MTG. SCREW	WEIGHT bs/100 pcs (g)/100 pcs	USE WITH ANY OF THESE CABLE TIES
TMEH-S8	-0	0.18 (4.6)	1.62	#8 (M4)	1.04 (471.4)	I,S,H,EH
TMEH-S10	-0	0.20	(41.1)	#10 (M5)	1.03 (467.4)	I,S,H,EH
IMEH-310	-100 -109	(5.1)	1.65			1939119211
TMEH-S25	-0	0.26 (6.6)	1.62 (41.1)	1/4" (M6)	1.01 (458.0)	I,S,H,EH



DESCRIPTION

DATE

BY СНК



*MATERIAL SUFFIX	MATERIAL							
-0	WEATHER RESISTANT NYLON							
-100 WEATHER RESISTANT POLYPROPYLE								

NOTES:

CHK.D

1. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE.

2. CABLE THE CROSS SECTION CODE:

1 = INTERMEDIATE, S=STANDARD

DIMENSIONS IN BRACKETS ARE METRIC [mm]

GB0239EL

H=HEAVY DUTY, EH=EXTRA HEAVY.

							G00239EL_PB_TMEH_02				
									CORP. TINLEY PARK, ILLINOIS	5	
									TMEH-XX		
									TIE MOUNT		
2	10/28/03	MSAE		ADDED SEPERATE TMEH-SIO ROW FOR -100 AND -109 PARTS, 0.50 (12,7) DIA WAS .52 (13,2), 'B' WAS 1.65 (41,9) FOR -0 PARTS, 0.72 (18,3) WAS .74 (18,8) 1.04 (28,4) WAS 1.05 (28,7)	GB0239EL	2			UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ±0.05 (1.31 (.XXX) ±0.010 (0.25) (.XX) ±0.02 (0.51 ANGLES ± 5°	10%	
1	7/24/01	LGG		ADDED REF & UPDATED	GB0239EL	1			DRIVEN BY AJV MAT'L:		
R	12/13/96	٧,٧		INITIAL RELEASE	GB0239EL	R			DATE 12/13/96 SEE TABLE COMMING NO.	DMG	

CUST

ECN - R

SUP