




Pass & Seymour



PTIG5362-LA



PTIG26362-LA



PT6STR PTR6STR

# TVSS & Isolated Ground PlugTail™ Isolated Ground Receptacles

2 Pole, 3 Wire Grounding, 15 & 20A, 125V

### Features

- .036 inch thick brass triple wire contacts for lasting retention.
- Impact-resistant nylon face.
- Corrosion-resistant plated steel straight strap for increased rigidity and strength.
- Auto-ground clip assures positive ground.
- No exposed terminals for a finger safe application.
- Ultrasonically welded polycarbonate connector housing secures terminations in a UL Listed finger safe housing.
- Pre-stripped connector leads.
- Nylon isolator plate for isolating ground from strap and box system.
- Crimped and welded contacts.

Catalog Number	Rating A. V.	NEMA Config. No.	Color	3rd Party Compliance	
				cULus	FSUL WC596
<b>Duplex Receptacles</b>					
PTIG5262-I	15 125	5-15R	Ivory	•	•
PTIG5262-W	15 125	5-15R	White	•	•
PTIG5262	15 125	5-15R	Orange	•	•
PTIG5262-GRY	15 125	5-15R	Gray	•	•
PTIG5262-RED	15 125	5-15R	Red	•	•
PTIG5262-LA	15 125	5-15R	Light Almond	•	•
PTIG5362-I	20 125	5-20R	Ivory	•	•
PTIG5362-W	20 125	5-20R	White	•	•
PTIG5362	20 125	5-20R	Orange	•	•
PTIG5362-GRY	20 125	5-20R	Gray	•	•
PTIG5362-RED	20 125	5-20R	Red	•	•
PTIG5362-LA	20 125	5-20R	Light Almond	•	•
<b>Decorator Duplex Receptacles</b>					
PTIG26262-I	15 125	5-15R	Ivory	•	•
PTIG26262-W	15 125	5-15R	White	•	•
PTIG26262	15 125	5-15R	Orange	•	•
PTIG26262-GRY	15 125	5-15R	Gray	•	•
PTIG26262-RED	15 125	5-15R	Red	•	•
PTIG26262-LA	15 125	5-15R	Light Almond	•	•
PTIG26362-I	20 125	5-20R	Ivory	•	•
PTIG26362-W	20 125	5-20R	White	•	•
PTIG26362	20 125	5-20R	Orange	•	•
PTIG26362-GRY	20 125	5-20R	Gray	•	•
PTIG26362-RED	20 125	5-20R	Red	•	•
PTIG26362-LA	20 125	5-20R	Light Almond	•	•

Catalog Number	Wire Type	Wire Length
<b>PlugTail Connectors*</b>		
PT6STR	Stranded	6"
PT6SOL	Solid	6"
<b>PlugTail Connectors – Right Angle*</b>		
PTRA6STR	Stranded	6"
PTRA6SOL	Solid	6"

\*All PlugTail Connectors are available in various Wire Lengths, please use Configurable Solutions to order.



NEMA 5-15R



NEMA 5-20R

Configurable Solutions for PlugTail Receptacles and Connectors, see Page U-1.