


PACKAGE DIMENSIONS inch (mm)



CASE 51 LENSED SIDELOOKER
CHIP ACTIVE AREA: .0082 in² (5.27 mm²)

PRODUCT DESCRIPTION

Planar silicon photodiode in a transfer molded, large lensed sidelooker package. The dark package material filters out visible light but passes infrared. These diodes exhibit low dark current under reverse bias and fast speed of response.

ABSOLUTE MAXIMUM RATINGS

Storage Temperature: -40°C to 85°C
 Operating Temperature: -40°C to 85°C

RoHS Compliant



ELECTRO-OPTICAL CHARACTERISTICS @ 25°C (See also VTP curves, pages 45-46)

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	VTP7840H			UNITS
			Min.	Typ.	Max.	
I _{SC}	Short Circuit Current	H = 100 fc, 2850 K	50	70		μA
TC I _{SC}	I _{SC} Temperature Coefficient	2850 K		.20		%/°C
V _{OC}	Open Circuit Voltage	H = 100 fc, 2850 K		325		mV
TC V _{OC}	V _{OC} Temperature Coefficient	2850 K		-2.0		
I _D	Dark Current	H = 0, VR = 10 V			20	nA
R _{SH}	Shunt Resistance	H = 0, V = 10 mV		0.25		GΩ
C _J	Junction Capacitance	H = 0, V = 3 V			40	pF
S _R	Sensitivity	@ Peak		.55		A/W
λ _{range}	Spectral Application Range		725		1150	nm
λ _p	Spectral Response - Peak			925		nm
V _{BR}	Forward Voltage	@ 10 mA		1.0		V
θ _{1/2}	Angular Resp. - 50% Resp. Pt.			±48		Degrees
NEP	Noise Equivalent Power			5.3 x 10 ⁻¹⁴ (Typ.)		W/√Hz
D*	Specific Detectivity			5.1 x 10 ¹² (Typ.)		cm√Hz/W

VTP Process Photodiodes

VTP PROCESS FAST RESPONSE, HIGH DARK RESISTANCE

FEATURES

- *Visible to enhanced IR spectral range*
- *Integral visible rejection filters available*
- *Response @ 940 nm, 0.60 A/W, typical*
- *-1 to 2% linearity over 7 to 9 decades*
- *Low dark currents*
- *High shunt resistance*
- *High reverse voltage rating*
- *Low capacitance*

PRODUCT DESCRIPTION

Photodiodes in this series have been designed for low junction capacitance. The lower the capacitance, the faster the response of the diode. Also, speed can be further increased by reverse biasing the diodes which lowers the capacitance even more.

These diodes have excellent response in the IR region and are well matched to IR LEDs. Responsivity is categorized at 940 nm (GaAs LED). Some diodes are available in packages which incorporate a visible rejection filter effectively blocking any light below 700 nm.

Diodes made with the VTP process are suitable for operation under reverse bias conditions but may be used in the photovoltaic mode. Typical reverse breakdown voltages are around 140 V. Low dark currents under reverse bias are also a feature of this series.