



PSA-A15W



15 Watt CEC Compliant Adapter

PSAA15W Single Output Series

Dimensions

Length: 81.2mm (3.20in)

Height: 29.8mm (1.17in)

Width: 50mm (1.97in)

Weight: 140g (4.94oz.)

MODEL	DC OUTPUT VOLTAGE	LOAD	
		Min.	Max.
PSAA15W-050	5V	0A	3A
PSAA15W-120	12V	0A	1.25A
PSAA15W-180*	18V	0A	0.83A
PSAA15W-240	24V	0A	0.63A
PSAA15W-480	48V	0A	0.31A



15 Watt Universal 2-Wire Input Desktop Adapter

PSAA15W Single Output Series Meets CEC and EISA Requirements



Features

- 0A Minimum Load
- Efficiency Level IV Compliance
- Class B EMI
- <0.25mA Leakage Current
- Compact Size

Applications

- Portable Equipment
- Peripherals and Terminals
- Low-power Computers
- Networking

Safety Approvals

- cUL/UL
- CE
- TUV
- Meeting Cal. Prop. 65

Mechanical Characteristics

- Length: 81.2mm (3.20in)
- Width: 50mm (1.97in)
- Height: 29.8mm (1.17in)
- Weight: 140g (4.94oz.)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max.)	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSAA15W-050	+5V	0A	3.0A	70mV	±5%	IV
PSAA15W-120	+12V	0A	1.25A	120mV	±5%	IV
PSAA15W-180	+18V	0A	0.83A	180mV	±5%	IV
PSAA15W-240	+24V	0A	0.63A	240mV	±5%	IV
PSAA15W-480	+48V	0A	0.31A	480mV	±5%	IV

(1) Measured by using a 12 inch twisted pair terminated with a 10uF capacitor and 0.1uF ceramic in parallel.

PSAA15W Characteristics

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Frequency
47 to 63Hz

Input Current
0.5A (rms) max. @ 120VAC
0.25A (rms) max. @ 240VAC

Leakage Current
0.25mA max.

Inrush Current (cold)
30A for 120VAC at max. load
60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
0.5W maximum at no load

OUTPUT:

Efficiency
> 74% average efficiency

Hold-up Time
10mS min. @ 120VAC and max. load

Over Voltage Protection
By Zener clamping, adapter will be shut down

Over Current Protection
Output equipped with short circuit protection – auto restart

Short Circuit Protection
Output can be shorted without damage

ENVIRONMENTAL:

Temperature
Operation 0 to +40°C
Non-operation -25 to +75°C

Humidity
Operation 20 to 90%

Emissions
FCC Class B
EN55022 Class B

Dielectric Withstand (Hi-pot) Test
Primary to Secondary: 3000VAC for 1 minute, 10mA

DC Output Connector
2.1x5.5mm Center Positive Standard

Mating Connector
Kycon KLD-0202-A or equivalent

Dimension Diagram Unit: mm

