



PSC03R



PSC03R SERIES
2.5 Watt USB Adapter with Interchangeable Plugs

Dimensions

Length: 75.32mm (2.97in)
Height: 31.67mm (1.25in)
Width: 45.96mm (1.81in)
Weight: 61.1g (2.16oz)

MODEL	DC OUTPUT VOLTAGE	LOAD	
		Min.	Max.
PSC03R-050	5V	0A	0.5A
US Plug: RPA	n/a	n/a	n/a
UK Plug: RPK	n/a	n/a	n/a
Europe Plug: RPE	n/a	n/a	n/a
Australia Plug: RPS	n/a	n/a	n/a
All 4 Plugs: RPKit	n/a	n/a	n/a



2.5W USB Adapter with Interchangeable Plugs PSC03R Adapter Meets CEC and EISA Requirements



Features

- USB Socket
- Field Changeable AC Plugs
- ECOC Compliance
- Low Leakage Current
- UL 94 Vo Flammability
- Efficiency Level IV Compliance

Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- Networking

Safety Approvals

- cUL/UL
- TUV
- SAA
- CE
- C-Tick

Mechanical Characteristics

- Length: 75.32mm (2.97in)
- Width: 45.96mm (1.81in)
- Height: 31.67mm (1.25in)
- Weight: 61.1g (2.16oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSC03R-050	5V	0A	0.5A	55mV	±5%		IV

Note: (1) Measured by using a 12-inch twisted pair terminal with a 10uf EC capacitor and a 0.1uf ceramic in parallel, measured at maximum load.

PSC03R Characteristics

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Current
0.15A(RMS) max. @ 115VAC
0.08A(RMS) max. @ 230VAC

Leakage Current
20uA max. @ 254VAC, 50Hz

Inrush Current (cold)
<30A for 120VAC at max. load
<60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
0.5W maximum at no load

OUTPUT:

Efficiency
> 58% average efficiency

Hold-up Time
10mS min. @ 120VAC and Max. load

Over-current Protection
0.75A max.

Over-Voltage Protection
8VDC max.

Short Circuit Protection

Output can be shorted without damage

Adapter Detection:

Each data line (Data+ and Data-) is tied to +VDC via a 7.5K Ohm resistor and to DC RTN via a 15K Ohm resistor

ENVIRONMENTAL:

Temperature

Operation 0 to +45°C
Non-operation -40 to +85°C

Humidity

Operation 10 to 90%

Emissions

FCC Part 15 Class B
CISPR 22 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC

AC Input Clips (sold separately)

US: RPA
Europe: RPE
UK: RPK
Australia: RPS

Dimension Diagram Unit: mm (inch)

