

PSM04A



PSM04A WALL PLUG ADAPTER
4 Watt Flip-Plug Compact Adapter

Dimensions

Length: 69.4mm (2.73in)
Height: 25mm (0.98in)
Width: 48mm (1.89in)
Weight: 145g (5.12oz)

MODEL	DC OUTPUT VOLTAGE	LOAD	
		Min.	Max
PSM04A-050(STD)	5V	0A	0.75A



4 Watt Flip-Plug Compact Adapter PSM04A Wall Plug Adapter Meets CEC and EISA Requirements



Features

- No Load Power Consumption < 0.5 Watt
- Flip Plug Design
- EISA Compliant*
- Low Leakage Current
- Low Cost

Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- PDA

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 69.4mm (2.73in)
- Width: 48mm (1.89in)
- Height: 25mm (0.98in)
- Weight: 145g (5.12oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSM04A-050(STD)	5V	0A	0.75A	55mV	±5%		

Note: (1) Measured with by-pass capacitors 0.1uf/10uf at output connector terminal and oscilloscope set at 20Mhz.

*EISA Compliant Level IV_{115VAC} III

PSM04A Characteristics

INPUT:

AC Input Voltage Rating

100 to 240VAC

AC Input Voltage Range

90 to 264VAC

AC Input Current

0.2A(RMS) Max.

Leakage Current

250uA Max.

AC Input Frequency

47-63Hz

Input Power Saving

0.5W Max.

OUTPUT:

Efficiency

50% Min.

Hold-up Time

10mS Min. @ 120VAC and Max. load

Over Voltage Protection

7.5V Max.

Short Circuit Protection

Protection against short circuit for output: the load current delivered into a short circuit shall not exceed 2A.

ENVIRONMENTAL:

Temperature

Operation 0 to +45°C

Non-operation -40 to +85°C

Humidity

Operation 10 to 90%

Emissions

FCC Part 15 Class B

CISPR 22 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC

DC Output Connector

2.1x5.5mm Center Positive Standard

Mating Connector

Kycon KLD-0202-A or equivalent

Dimension Diagram Unit: mm (inch)

