

UK 1,5 N RD

Order No.: 0719032

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=0719032>Universal terminal block with screw connection, cross section: 0.14 -
1.5 mm², width: 4.2 mm, color: Red

Commercial data

| | |
|----------------|---------------|
| EAN | 4017918591434 |
| Pack | 50 Pcs. |
| Customs tariff | 85369010 |
| Weight/Piece | 0.00581 KG |

Product notes

WEEE/RoHS-compliant since:
01/01/2003

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Certificates / Approvals

Approval logo



requested approbations

| | |
|-------------------|----------------|
| Certification | GL |
| Certification Ex: | IECEX, KEMA-EX |

| Accessories | | |
|--------------------|-------------------------------|---|
| Item | Designation | Description |
| Assembly | | |
| 3003224 | ATP-UK | Separating plate, for visual and electrical separation of terminal groups, width: 1.5 mm, color: Gray |
| 3022218 | CLIPFIX 35 | Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 mounting rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip marker KLM 2 and KLM, width: 9.5 mm, color: gray |
| 3001022 | D-UK 2,5 | Cover, width: 1.5 mm, color: gray |
| 3001103 | D-UK 2,5 BU | Cover, width: 1.5 mm, color: blue |
| 1201442 | E/UK | End clamp, for supporting the electronic base. If mounted vertically, 2 end clamps are required in each case |
| 1201028 | NS 32 AL UNPERF 2000MM | G rail 32 mm (NS 32) |
| 1201280 | NS 32 CU/120QMM UNPERF 2000MM | G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m |
| 1201358 | NS 32 CU/35QMM UNPERF 2000MM | G-profile DIN rail, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m |
| 1201002 | NS 32 PERF 2000MM | G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m |
| 1201015 | NS 32 UNPERF 2000MM | G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m |
| 0801762 | NS 35/ 7,5 CU UNPERF 2000MM | DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m |
| 0801733 | NS 35/ 7,5 PERF 2000MM | DIN rail, material: Steel, perforated, height 7.5 mm, width 35 mm, length: 2 m |
| 0801681 | NS 35/ 7,5 UNPERF 2000MM | DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m |
| 1201756 | NS 35/15 AL UNPERF 2000MM | DIN rail, deep-drawn, high profile, unperforated, 1.5 mm thick, material: Aluminum, height 15 mm, width 35 mm, length 2 m |
| 1201895 | NS 35/15 CU UNPERF 2000MM | DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m |
| 1201730 | NS 35/15 PERF 2000MM | DIN rail, material: Steel, perforated, height 15 mm, width 35 mm, length: 2 m |
| 1201714 | NS 35/15 UNPERF 2000MM | DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m |
| 1201798 | NS 35/15-2,3 UNPERF 2000MM | DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m |
| Bridges | | |
| 3001569 | FBRN 4-4 N | Fixed bridge, 4-pos. |
| 3001572 | FBRN 5-4 N | Fixed bridge, 5-pos. |

| | | |
|---------|-------------|--|
| 3001585 | FBRN 6-4 N | Fixed bridge, 6-pos. |
| 3001598 | FBRN 7-4 N | Fixed bridge, 7-pos. |
| 3001608 | FBRN 8-4 N | Fixed bridge, 8-pos. |
| 3001624 | FBRN 10-4 N | Fixed bridge, for cross connections in the terminal center, with fixed crimped rolls, screw heads without insulation, 10-pos., divisible |
| 3001637 | FBRN 20-4 N | Fixed bridge, 20-pos. |

Marking

| | | |
|---------|-------------|---|
| 0805823 | ZB 4:SO/CMS | Zack strip, 10-section, divisible, special printing, marking according to customer requirements |
|---------|-------------|---|