

## UK 2,5 N GN

Order No.: 0719087

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=0719087>

Universal terminal block with screw connection, cross section: 0.2 - 2.5 mm<sup>2</sup>, AWG: 24 - 12, width: 5.2 mm, color: green



### Commercial data

|                |               |
|----------------|---------------|
| EAN            | 4017918599447 |
| Pack           | 50 Pcs.       |
| Customs tariff | 85369010      |
| Weight/Piece   | 0.006427 KG   |

### Product notes

WEEE/RoHS-compliant since:  
01/01/2003



<http://>

[www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Certificates / Approvals

#### Approval logo



#### requested approbations

|                   |                           |
|-------------------|---------------------------|
| Certification     | CB, GL, GOST, KEMA        |
| Certification Ex: | FM, GL-EX, IECEx, KEMA-EX |

| Accessories     |                               |   |
|-----------------|-------------------------------|---|
| Item            | Designation                   | Description   |
| <b>Assembly</b> |                               |   |
| 3003224         | ATP-UK                        | Separating plate, for visual and electrical separation of terminal groups, width: 1.5 mm, color: Gray   |
| 3022218         | CLIPFIX 35                    | Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 mounting rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip marker KLM 2 and KLM, width: 9.5 mm, color: gray |
| 3001022         | D-UK 2,5                      | Cover, width: 1.5 mm, color: gray   |
| 1201442         | E/UK                          | End clamp, for supporting the electronic base. If mounted vertically, 2 end clamps are required in each case  |
| 0201595         | FB-150 METER                  | Cross connection rail, for fixed bridging of identical inputs and outputs, made of Cu, nickel-plated, 1 m long  |
| 1201028         | NS 32 AL UNPERF 2000MM        | G rail 32 mm (NS 32)  |
| 1201280         | NS 32 CU/120QMM UNPERF 2000MM | G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m   |
| 1201358         | NS 32 CU/35QMM UNPERF 2000MM  | G-profile DIN rail, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m   |
| 1201002         | NS 32 PERF 2000MM             | G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m  |
| 1201015         | NS 32 UNPERF 2000MM           | G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m  |
| 0801762         | NS 35/ 7,5 CU UNPERF 2000MM   | DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m   |
| 0801733         | NS 35/ 7,5 PERF 2000MM        | DIN rail, material: Steel, perforated, height 7.5 mm, width 35 mm, length: 2 m  |
| 0801681         | NS 35/ 7,5 UNPERF 2000MM      | DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m  |
| 1201756         | NS 35/15 AL UNPERF 2000MM     | DIN rail, deep-drawn, high profile, unperforated, 1.5 mm thick, material: Aluminum, height 15 mm, width 35 mm, length 2 m   |
| 1201895         | NS 35/15 CU UNPERF 2000MM     | DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m  |
| 1201730         | NS 35/15 PERF 2000MM          | DIN rail, material: Steel, perforated, height 15 mm, width 35 mm, length: 2 m   |
| 1201714         | NS 35/15 UNPERF 2000MM        | DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m   |
| 1201798         | NS 35/15-2,3 UNPERF 2000MM    | DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m   |
| 2770215         | TS-KK 3                       | Separating plate, for electrical separation of neighboring bridges, can be fitted later, no loss of pitch, color: Gray  |
| 2303608         | ZSR                           | Distance piece, metal, for branches of FB-150, with screw and thrust washer   |

**Bridges**

|         |             |  |
|---------|-------------|--|
| 2303145 | EBL 2- 5    | Insertion bridge, 2-pos., fully insulated  |
| 2303158 | EBL 3- 5    | Insertion bridge, 3-pos., fully insulated  |
| 2303132 | EBL 10- 5   | Insertion bridge, 10-pos., divisible, fully insulated  |
| 3000227 | FBRI 2-5 N  | Fixed bridge, for cross connections, with screws, screw heads without insulation, 2-pos.   |
| 2770642 | FBRI 10-5 N | Fixed bridge, for cross connections in the terminal center, with fixed crimped rolls, screw heads with insulating collar as shock protection, 10-pos., divisible |
| 3000434 | FBRI 12-5 N | Fixed bridge, for cross connections in the terminal center, with fixed crimped rolls, screw heads with insulating collar as shock protection, 12-pos.            |
| 3000476 | FBRI 16-5 N | Fixed bridge, for cross connections in the terminal center, with fixed crimped rolls, screw heads with insulating collar as shock protection, 16-pos.            |
| 3000515 | FBRI 20-5 N | Fixed bridge, for cross connections in the terminal center, with fixed crimped rolls, screw heads with insulating collar as shock protection, 20-pos.            |
| 3006823 | FBRI 40-5 N | Fixed bridge, for cross connections in the terminal center, with fixed crimped rolls, screw heads with insulating collar as shock protection, 40-pos.            |
| 1413230 | SBRN 2-7    | Switching bridge, 2-pos.   |
| 2303239 | USBR 2-7    | Switching bridge, 2-pos.   |
| 2305538 | USBRJ 2-7   | Switching bridge, for bridged terminal groups, 2-pos.  |

**Marking**

|         |                  |   |
|---------|------------------|---|
| 1007219 | SBS 5:UNBEDRUCKT | Marker cards for modular terminal blocks, color: white  |
| 0805357 | WS 3- 5          | Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 5 mm                      |
| 0805344 | WS 4- 5          | Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 5 mm                      |
| 0805331 | WS 5- 5          | Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 5 mm                      |
| 1050295 | ZB 5:SO/CMS      | Zack strip, 10-section, divisible, special printing, marking according to customer requirements |

**Plug/Adapter**

|         |            |   |
|---------|------------|---|
| 2303543 | KSS 5      | Short circuit connector, for short circuiting neighboring terminal blocks, can only be used with PSB or PSBJ, 2-pos., pitch: 5.2 mm, color: Black |
| 0201744 | MPS-MT     | Test plug, consisting of: Metal part for 2.3 mm diameter socket hole  |
| 0601292 | PSB 3/10/4 | Test plug socket, not insulated, length: 10 mm, screw thread width: 3 mm, socket width: 4 mm  |

|         |             |   |
|---------|-------------|---|
| 0201304 | PSBJ 3/13/4 | Test plug socket, insulated, length: 13 mm, screw thread width: 3 mm, socket width: 4 mm, insulation material transparent |
| 0201647 | RPS         | Reducing plug, for transition from 4 mm diameter test plug socket, insulation: gray                                       |