


Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

▶ Extract from the online catalog



Marker for thermal transfer printer, perforated 1-way, white, labeling field: 25 x 5 mm, can be used for 2.4 mm diameter, shrinkage ratio 3:1, 1 roll = 500 Marker at 25 mm

Order No.	0816294
Ord designation	WMS 2,4 (25X5)R
EAN	4046356108492
Pack	1 Pcs.
Customs tariff	39269097
Weight/Piece	0.2968 KG
Catalog page information	Page 464 (CL-2007)

▶ Product notes

WEEE/RoHS-compliant since: 06/07/2006



IMPORTANT : This date is valid for Customers in Germany only. Date Format is MM/DD/YYYY. Please contact your local in-country Phoenix Contact location or designated business partner for a Logistics Compliant date in your area. In order to guarantee delivery of RoHS-Compliant product, please purchase Phoenix Contact parts from authorized Phoenix Contact representatives and distributors.

▶ Technical data

General

Length	50 mm
Width	5 mm

WMS 2,4 (25X5)R



Color	white
Base element material	polyolefine
Wipe resistance	DIN EN 61010-1/VDE 0411-1
Ambient temperature (operation)	-55 °C ... 135 °C
Components	Silicone-free
Material	Polyolefine

► Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>
Phoenix Contact
Technical modifications reserved;