
#### WMS 9,5 (25X16)R



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at http://www.download.phoenixcontact.com. The General Terms and Conditions of Use apply to Internet downloads.

### Extract from the online catalog



Marker for thermal transfer printer, perforated 1-way, white, labeling field:  $25 \times 16$  mm, can be used for 9.5 mm diameter, shrinkage ratio 3:1, 1 roll = 500 Marker at 25 mm

Order No. Ord designation

EAN Pack Customs tariff Weight/Piece Catalog page information WMS 9,5 (25X16)R 4046356108515

0817413

1 Pcs. 39269097 0.405 KG Page 464 (CL-2007)

### Product notes

WEEE/RoHS-compliant since:

IMPORTANT : This date is valid for Customers in Germany only. Date Format is MM/DD/YYYY.Please contact your local in-country Phoenix Contact location or designated business partner for a Logistics Compliant date in your area.In order to guarantee delivery of RoHS-Compliant product, please purchase Phoenix Contact parts from authorized Phoenix Contact representatives and distributors.

#### 04/21/2006



## Technical data

| General |       |  |
|---------|-------|--|
| Length  | 50 mm |  |
| Width   | 16 mm |  |
|         |       |  |

PHOENIX CONTACT Inc., USA http://www.phoenixcon.com

Page 1/4 Jun 26, 2007

### WMS 9,5 (25X16)R

Color Base element material Wipe resistance Ambient temperature (operation) Components Material



white polyolefine DIN EN 61010-1/VDE 0411-1 -55 °C ... 135 °C Silicone-free Polyolefine





# Address

PHOENIX CONTACT Inc., USA 586 Fulling Mill Road Middletown, PA 17057 USA Phone (800) 888-7388 Fax (717) 944-1625 http://www.phoenixcon.com Phoenix Contact Technical modifications reserved;