

Search

1534630 SACC-DSIV-M12FSD-4CON-L90

- Advanced Search
- Search Assistants
- Product catalog**
- Industrial Connection Technology
CLIPLINE
- ▶ **Field cabling
PLUSCON**
- PCB Connection Systems
COMBICON
- Surge protection
TRABTECH
- Signal Converters
INTERFACE
- Components and Systems
AUTOMATION
- My functions
- Call back
- Login



Information on this item

- ▶ Item homepage
- ▶ **Technical data**
- ▶ Catalog Extract (PDF)
- ▶ Diagrams/Drawings
- ▶ Downloads



- ▶ Back to navigation
- ▶ Show comparison

Technical data

General data

Nominal current I_N	4 A
Nominal voltage U_N	250 V
Number of positions	4
Volume resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Ambient temperature (operation)	-25 °C ... 85 °C

General characteristics

Coding	D - data
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 66
Material, knurls	Nickel-plated brass
Sealing material	NBR
Mounting type	Rear mounting M12 x 1 With locking nut
Type of connection	Solder pins
Status display	No