

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at http://www.download.phoenixcontact.com. The General Terms and Conditions of Use apply to Internet downloads.

## ▶ Extract from the online catalog



RJ45 connector, IP67, CAT5e, 8-pos., with QUICKON fast connection technology, for 1-wire and 7-wire conductors AWG 26 ... 22, for cable cross section 5.0 mm ... 8.0 mm, color: gray

Order No. 1656990

Ord designation VS-08-RJ45-5-Q/IP67

EAN 4046356081399

 Pack
 1 Pcs.

 Customs tariff
 85366990

 Weight/Piece
 0.0323 KG

Catalog page information Page 170 (PC-2007)

#### ▶ Product notes

WEEE/RoHS-compliant since:

10/20/2006



IMPORTANT: This date is valid for Customers in Germany only. Date Format is MM/DD/YYYY.Please contact your local in-country Phoenix Contact location or designated business partner for a Logistics Compliant date in your area. In order to guarantee delivery of RoHS-Compliant product, please purchase Phoenix Contact parts from authorized Phoenix Contact representatives and distributors.



## ▶ Technical data

#### VS-08-RJ45-5-Q/IP67



Mechanical characteristics

Ambient temperature (operation) -20 °C ... 70 °C

Insertion/withdrawal cycles ≥ 1000

Type of connection IDC fast connection External cable diameter 5 mm ... 8 mm

Material data

Housing material PA

Contact carrier material PC

Material of contact Copper alloy
Material of contact surface Gold over nickel

Material, O-ringFPMCable seal materialNBRMaterial, housing intermediate sealNBRDegree of protectionIP67

**Electrical characteristics** 

Inflammability class acc. to UL 94

Number of positions 8


Transmission characteristics (category) CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)

V0



# **▶** Drawings

### **Dimensioned drawing**



RJ45 plug connector, IP67

Logo

# **Ethernet**



# ► Accessories

Item <b>Marking</b>	Designation	Description
0814775	VS-ZBFM-8-SET	Marker label set, consisting of 4 sheets (white, blue, yellow, orange) each with 50 labels for color marking of sleeve housings and panel mounting frames with IP67 protection



## **▶** Address

PHOENIX CONTACT Inc., USA 586 Fulling Mill Road Middletown, PA 17057 USA Phone (800) 888-7388 Fax (717) 944-1625 http://www.phoenixcon.com Phoenix Contact Technical modifications reserved;