

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

► Extract from the online catalog



Sensor/actuator box, without LED, with master cable, markers and double-occupied slots

The illustration shows a version with 8 slots

Order No.	1680885
Ord designation	SACB-4/ 8- 5,0PUR
EAN	4017918171162
Pack	1 Pcs.
Customs tariff	85445190
Catalog page information	Page 128 (PC-2005)

► Technical data

General data

Nominal voltage U_N	120 V DC
Nominal voltage U_N	120 V AC
Max. operating voltage U_{max}	135 V DC
Max. operating voltage U_{max}	135 V AC
Ambient temperature (operation)	-25 ° C ... 75 ° C
Degree of protection	IP65/IP67
Number of positions	5
Max. current carrying capacity per path	2 A
SACB total current	12 A
Number of slots	4
Sensor/actuator connection system	M 12 female connector

Master cable data

Type of connection	Fixed connection
Fixed cable length	5 m
Cable type	Master cable suitable for flexible cable conduit
Ambient temperature (operation)	-30 ° C ... 90 ° C (for fixed installation)
Ambient temperature (operation)	-5 ° C ... 70 ° C (for flexible installation)
Signal line cross section, flexible	0.5 mm ² (double-occupancy)
Power supply cross section, flexible	1 mm ² (3x)
External diameter	9.3 mm
AWG power supply	17
AWG signal line	24

Insulation material

Insulating material	PA 6.6
Inflammability class acc. to UL 94	V0

► **Certificates**

CUL



Nominal voltage U_N	120 V
AWG/kcmil	22-16

UL

Nominal voltage U_N	120 V
AWG/kcmil	22-16

► Drawings

Schematic diagram



Approval logo



► **Accessories**

Item	Designation	Description
Assembly		
1680539	PROT-M12	Sealing cap for closing unoccupied connections M12

► **Address**

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>
Phoenix Contact
Technical modifications reserved;