

VS-08-LI-VSIP67-RJ45-CF-5,0

Order No.: 1689598



Assembled Ethernet cable, CAT5e, shielded, 2-pair, AWG 26 stranded (7-wire), line, RAL 5021 (water blue), RJ45/IP67 on RJ45, length: 5 m

Ethernet**Commercial data**

EAN	4017918907532
Pack	1 Pcs.
Customs tariff	85369010
Weight/Piece	0.2328 KG
Catalog page information	Page 172 (PC-2007)

Product notes

WEEE/RoHS-compliant since:
08/29/2006

**Technical data****Mechanical characteristics**

Number of positions	4
Shielded	Yes
Insertion/withdrawal cycles	≥ 750
Cable diameter	5.80 mm
Cable structure	2x2xAWG26/7; SF/UTP

Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	78 mm
Length of cable	5 m
Ambient temperature (operation)	-30 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 60 °C (cable, flexible installation)
	(plug/socket)

Material data

Housing material	PA
Contact carrier material	Thermoplastic
Contact material	Copper alloy
Contact surface material	Gold over nickel
Material, O-ring	FPM
Cable seal material	NBR
Outer sheath, material	Halogen-free compound, HM 2 in acc. with VDE 0207
External sheath, color	water blue RAL 5021
Degree of protection	IP67/IP20

Electrical characteristics

Rated voltage (III/3)	60 V
Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)

Accessories

Item	Designation	Description
Protective covers		
1653757	VS-SCRJ-PC	IP67 protective cover, for covering the male inserts in the sleeve housings IP67, VS-SCRJ-..., VS-04-..., VS-06-... and VS-08-...