



#### **PRODUCTS**

Series



**CROSS-REFERENCE** 

Print

# Þ

#### **Plug-in Screw Connector Systems for Printed Circuit Boards**

TYPE 971-SLT-SMD
5 mm spacing - 2 to 12 poles
Distributor Stock Check

Download PDF



Color specifications

RoHS WEEE	- EN NESS





3D Model

Can plug with

How to order


#### **Description**

U.S. Pat.6,224,399B1

- Pinstrip
- low profile
- Plug-In Direction Perpendicular to PCB and Wire Entrance Parallel to PCB when plugged with 950-NAF-DS, 950-NLFL-DS, 958-NLFL-DS, 950-FL-DS, 950-T-FL-DS, 115-F-111, 115-F-118 and 115-F-211
- Exceptional pin retention force on SMT
- Typical resistance to horizontal peel off force per 2 poles: 15 kgf (33 lbf), per 6 poles: 28 kgf (61 lbs) (depending on soldering process).

#### **Technical Data**

Center to Center Spacing: 5 mm (0.197 in.)



### Dimensions: mm (in.)

(A) Odd numbers of poles

(B) Even numbers of poles

(C) PCB Pad layout

Recommended Stencil Thickness: 0.15 mm (0.006 in.)

When locating connector, allow 0.5 mm clearance around it for process-induced variations.

## UL File No.E69841 CSA File No.LR24322

Rating	Current(A)	Voltage(V)	Application group	AWG
UL	10	300	В	
CSA	10	300	В	

#### Material

Molding: Polyamide 4.6, 30% GF (glass fiber reinforced), self extinguishing UL 94, V-0, color Black

Temperature limits:

**Short Time**: 260°C (500°F) Continuous: RTI 105°C (221°F) **Low Limit**: -40°C (-40°F)

Comparative Tracking Index: CTI > 250

Oxygen Index Rating: 37 %

Average weight: 0.1 gram,

Solder Pin: Ø 1.1 mm (0.04 in.), Tin plated copper

alloy

Top of page

### How to order

Item 971-SLT-SMD

**Options** 

G05: Gold Plating (5 micro inches)

G30: Gold Plating (30 micro inches) S30: Silver Plating (30 micro inches)

TR: Tape and Reel Assembly PCP: Removable Pick Cap

Note: Plated component: solder pin

Ordering Note: This product is currently available in Tape and Reel in 6 poles only.

For other configuration, please contact factory.

POLES: 02 to 12

971-SLT-SMD/

Request sample Request quote

Quantity

**Accessories** 

Add to shopping cart

2008, WECO Electrical Connectors Inc.

ISO 9001 registered quality management system