

NLC-COM-ENET-MB1

Order No.: 2701124

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2701124>

Ethernet communication module. Allows the nanoLine controller to be connected to an Ethernet, operating as a Modbus TCP Server.

Commercial data	
EAN	4046356325295
Pack	1 pcs.
Customs tariff	85176200
Weight/Piece	0.1443 KG
Catalog page information	Page 260 (NTK-2008)

Product notes

WEEE/RoHS-compliant since:
04/18/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Adds Ethernet connectivity (Modbus TCP Server functionality) to nanoLine controller. Attaches to left-side of base unit.

Technical data**Interfaces**

Interface	Ethernet 10/100 Base T
Type of connection	RJ45

Transmission speed	10/100 Mbps (autonegotiation)
Transmission length	100 m
Signal LEDs	LNK/ACT; Module; Network

Supply

Connection supply	Screw connection
Supply voltage	24 V DC (Power available via base unit)
Max. current consumption	180 mA (at 18 V DC)
Typical current consumption	110 mA

General data

Width	40 mm
Height	103.5 mm
Depth	43 mm
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;