

NLC-MOD-RTC

Order No.: 2701153

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2701153>

Real-time clock

Commercial data

EAN	4046356324663
Pack	1 pcs.
Customs tariff	91109000
Weight/Piece	0.0362 KG
Catalog page information	Page 263 (NTK-2008)

Product notes

WEEE/RoHS-compliant since:
04/18/2008

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces

Interface	Real-Time Clock
Type of connection	Slot 2

Supply

Supply voltage	24 V DC (Power available via base unit)
Max. current consumption	10 mA

Typical current consumption	4 mA
Realtime clock	
Realtime clock	Yes (battery-backed)
Accuracy real-time clock	5 s/year at 25 °C
	11 s/year overall (25°C to 55°C)
Battery	Life 5 years
General data	
Width	24.5 mm
Height	25.5 mm
Depth	49 mm
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Accessories

Item	Designation	Description
General		
2701292	NLC-MOD-CAP-PXC	Replacement cover for slot 2 in base unit.

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;