

NLC-MOD-RS232

Order No.: 2701179

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2701179>

RS-232 connection for data transfer or software configuration

Commercial data

EAN	4046356324649
Pack	1 pcs.
Customs tariff	85366990
Weight/Piece	0.0382 KG
Catalog page information	Page 261 (NTK-2008)

Product notes

WEEE/RoHS-compliant since:
04/18/2008

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Slot 1 option module. Connects the nanoLine controller to an RS-232 device. Transfers application or data or both.

Technical data

Interfaces

Interface	RS-232
Type of connection	RJ11, shielded
Transmission length	4 m (@115 kbaud)

Supply

Supply voltage	24 V DC (Power available via base unit)
Max. current consumption	18 mA
Typical current consumption	10 mA

General data

Width	24.5 mm
Height	25.5 mm
Depth	49 mm
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Accessories

Item	Designation	Description
------	-------------	-------------

General

2701289	NLC-MOD-CAP	Replacement cover for slot 1 in base unit.
2701234	NLC-PC/SERIAL-CBL 1M	Cable , serial

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;