

VAL-SQ CC 40-120/240S

Order No.: 2803991



Surge protection device for 120/240 V AC split phase configuration
 Uses a compact, NEMA rated enclosure that connects easily to an existing enclosure. Hybrid Sine Wave Tracking provides 40 kA surge protection.

Commercial data

EAN	4046356317115
Pack	1 pcs.
Customs tariff	85363030
Weight/Piece	2.074 KG

Product description

Surge protection device for 120/240 V AC systems with 40 kA protection

Technical data

Standards

Housing material	Metal
Degree of protection	IP40 / NEMA 1
Mounting type	3/4 inch NPT male
Design	Parallel hybrid
Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	3658 m
Message surge protection faulty	Optical

Direction of action	3L-N & N-GND
Width	190.00 mm
Height	108.00 mm
Length	63.00 mm

Protective circuit

Arrester rated voltage U_c	150 V
Response time	< 1 ns

Connection, protective circuit

Type of connection	#10 AWG/5.26 mm ² wires (24 in./61 cm long)
Connection system	4-wire + Gnd
Conductor cross section AWG/kcmil min.	10
Conductor cross section AWG/kcmil max	10

Environmental conditions

Standards/regulations	UL 1449 2 nd edition, February 2007
	UL 1283
	IEEE C62.41
	IEEE C62.45

NEMA / UL data

NEMA / UL data	type 2
short circuit current rating (SCCR)	22 kA
UL type	type 2
Voltage (L-L)	800 V
Voltage (N-G)	400 V
Voltage (L-G)	800 V
Voltage (L-N)	500 V
Maximum Circuit Breaker	30 A
Maximum Surge Current per Phase	40 kA

Certificates / Approvals

Certification	CUL Listed, GOST, UL Listed
---------------	-----------------------------