

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

► Extract from the online catalog

Memory module, 2 port twisted pair module for saving the switch configuration



Order No.	2832483
Ord designation	FL IF MEM 2TX-D
EAN	4017918974497
Pack	1 Pcs.
Customs tariff	85389091
Weight/Piece	0.0918 KG
Catalog page information	Page 212 (AX-2007)

► Technical data

Interfaces

Interface	Ethernet 10/100 Base T
No. of ports	2
Type of connection	RJ45 female connector
Transmission physics	Copper
Transmission speed	10/100 MBit/s
Transmission length	100 m

Function

Basic functionality	Configuration memory (plug-in)
---------------------	--------------------------------

Supply voltage

Supply voltage

(via head station)

Typical current consumption

10 mA

General data

Weight	70 g
Width	31 mm
Height	78 mm
Depth	72.5 mm
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Housing material	PA
Electromagnetic compatibility	Conformance with EMC directive 89/336/EEC
Emitted interference	EN 61000-6-3/-4
Immunity to interference	EN 61000-6-2

Conformity with EMC directives

Developed in acc. with standard	IEC 61000-6.2
Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion A
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test standard	IEC 61000-4-8 (immunity to magnetic fields)
Test result	Criterion A
Test standard	EN 55022 (emitted interference)
Test result	Criterion A

► Drawings

Logo

Ethernet

► Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>
Phoenix Contact
Technical modifications reserved;