

EMD-SL-PH-400

Order No.: 2866077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866077>

Electronic monitoring relay for phase sequence and phase failure monitoring

Commercial data	
EAN	4017918952679
Pack	1 Pcs.
Customs tariff	85364900
Weight/Piece	0.1555 KG
Catalog page information	Page 557 (IF-2007)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Increasingly higher demands are being placed on safety and system availability – across all sectors. Processes are becoming more and more complex, not only in mechanical engineering and the chemical industry, but also in plant and automation technology. Demands on power engineering are also increasing constantly.

Error-free and therefore cost-effective operation can only be achieved through continuous monitoring of important network and system parameters. Electronic monitoring relays in the EMD series are available for a wide range of monitoring tasks to avoid the consequences of errors or to keep them within limits.

The operating states are indicated using colored LEDs, errors that may occur can be sent to a control system via a floating contact or can shut down a part of the system. Some device versions are equipped with startup and response delays in order to briefly tolerate measured values outside the set monitoring range.

Technical data

Input data	
Nominal input voltage U_N	400 V (3 N ~ 400/230 V)

Function	Phase sequence, phase failure, asymmetry
Setting range for response delay	≤ 350 ms (fixed setting)
Setting range for starting delay	≤ 500 ms (fixed setting)
Asymmetry	Fixed, approx. 30%
Recovery time	< 100 ms
Contact side	
Contact type	2 floating PDT contacts
Maximum switching voltage	250 V AC (in acc. with IEC 60664-1)
Interrupting rating (ohmic load) max.	750 VA (3 A/250 V AC, module aligned, ≤ 5 mm spacing) 1250 VA (5 A/250 V AC, module not aligned, ≥ 5 mm spacing)
Output fuse	5 A (fast-blow)
Power supply	
Supply voltage	(From the measured voltage)
General data	
Width	22.5 mm
Height	113 mm
Length	90 mm
Service life mechanical	Approx. 2×10^7 cycles
Operating mode	100% operating factor
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Mounting position	Any
Assembly instructions	on TS 35 profile rail acc. to EN 60715
Pollution degree	3
Surge voltage category	III
Housing insulation material	Polyamide PA, self-extinguishing
Color	green
Rated surge voltage	4 kV (basic insulation)
Conformity	CE compliant
UL, USA / Canada	UL/C-UL listed UL 508
Connection data	
Conductor cross section stranded min.	0.25 mm ²
Conductor cross section stranded max.	2.5 mm ²

Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	14
Stripping length	8 mm
Type of connection	Screw connection

Certificates / Approvals



Certification

CUL Listed, UL Listed

Drawings

Block diagram

