

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

▶ Extract from the online catalog

Interface module



Order No.	2884033
Ord designation	FL IF 2FX ST-D
EAN	4046356049498
Pack	1 Pcs.
Customs tariff	85176200
Weight/Piece	0.0966 KG
Catalog page information	Page 213 (AX-2007)

▶ Technical data

Interfaces

Interface	Ethernet: 100Base-FX in acc. with IEEE 802.3
Transmission speed	100 MBit/s
Transmission length	10000 m (maximum (depends on the fiber used))
Interface	Ethernet: 100Base-FX in acc. with IEEE 802.3
No. of ports	2
Type of connection	ST BFOC
Transmission speed	100 MBit/s
Transmission length	10000 m (glass fiber with F-G 62.5/125 0.7 dB/km F1000)
Transmission length	6400 m (glass fiber with F-G 50/125 0.7 dB/km F1200)

FL IF 2FX ST-D



Transmission length	3000 m (glass fiber with F-G 62.5/125 2.6 dB/km F600)
Transmission length	2800 m (glass fiber with F-G 50/125 1.6 dB/km F800)

Function

Basic functionality	Media module for modular managed switch
---------------------	---

Supply voltage

Supply voltage	(via head station)
Typical current consumption	200 mA

General data

Weight	80 g
Width	31 mm
Height	83 mm
Depth	72.5 mm
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Housing material	PA
Electromagnetic compatibility	Conformance with EMC directive 89/336/EEC
Emitted interference	EN 61000-6-3/-4
Immunity to interference	EN 61000-6-2

Conformity with EMC directives

Developed in acc. with standard	IEC 61000-6.2
Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion A
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test standard	IEC 61000-4-8 (immunity to magnetic fields)
Test result	Criterion A
Test standard	EN 55022 (emitted interference)
Test result	Criterion A

► Drawings

Logo

Ethernet

► Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>
Phoenix Contact
Technical modifications reserved;