

RAD-OUT-2D-CNT

Order No.: 2885236



Digital expansion module with 2 digital outputs for output of pulses and frequencies



| Commercial data | |
|--------------------------|---------------------|
| EAN | 4046356049870 |
| Pack | 1 pcs. |
| Customs tariff | 85177090 |
| Weight/Piece | 0.1651 KG |
| Catalog page information | Page 251 (NTK-2008) |

Product notes

WEEE/RoHS-compliant since:



| Technical data | |
|---|------------------|
| General data | |
| Ambient temperature (operation) | -20 °C ... 65 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Degree of protection | IP20 |

| | |
|-----------------------|--|
| Mounting position | Any |
| Assembly instructions | on TS 35 profile rail acc. to EN 60715 |
| Housing material | Polyamide PA non-reinforced |
| Length | 99 mm |
| Width | 22.5 mm |
| Height | 114.5 mm |
| Conformity | CE compliant |
| ATEX approval | Ex II 3 G Ex nAC IIC T5 X |
| UL, USA / Canada | Class I, Div. 2, Groups A, B, C, D |

Connection data

| | |
|--|---------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 4 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 14 |
| Type of connection | Screw connection |
| Stripping length | 8 mm |
| Screw thread | M3 |

Certificates / Approvals

Certification Ex: CUL-EX LIS, UL-EX LIS

Drawings

Block diagram

