

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

## ► Extract from the online catalog

ST-COMBI connector, not bridgeable



The illustration shows a 6-position version

Order No.	3040274
Ord designation	SP 2,5/ 3
EAN	4017918832803
Pack	50 Pcs.
Customs tariff	85369010
Catalog page information	Page 114 (CL-2005)

## ► Certificates

---

Certificate logos



---

**CUL**

Nominal voltage $U_N$	300 V
Nominal current $I_N$	20 A
AWG/kcmil	26-12

---

**UL**

Nominal voltage $U_N$	300 V
Nominal current $I_N$	20 A
AWG/kcmil	26-12

---

## ► Drawings

---

### Diagram

---

---

## ► Accessories

---

Item	Designation	Description
<b>Assembly</b>		
3040559	PR	Snap-lock device, for plugs, 1-pos.
3040630	PR/2	Snap-lock device, for plugs, 2-pos.
3040614	PRZ	Snap-lock device and strain relief, for plugs, 2-pos.
3040591	PSH 3- 6	Shielding, for mounting on PZ/... and PRZ, for cables with 3-6 mm diameter
3040601	PSH 5-10	Shielding, for mounting on PZ/... and PRZ, for cables with 5-10 mm diameter
3040627	PZ/2	Strain relief, for SP ... and SPB ... plugs, 2-pos.
3040643	PZ/4	Strain relief, for SP ... and SPB ... plugs, 4-pos.
<b>Plug/Adapter</b>		
3002843	ISH 2,5/0,2	Insulation stop sleeve, color: White
3002856	ISH 2,5/0,5	Insulation stop sleeve, color: gray
3002869	ISH 2,5/1,0	Insulation stop sleeve, color: black

---

## ► Address

---

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057  
USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>  
Phoenix Contact  
Technical modifications reserved;