



PART NO.		MATERIAL:	"A" REF.	"B" REF.	"C" REF.	PANEL THICKNESS RANGE	"GAP" REF.
SOLID LENGTHS	SERRATED LENGTHS						
NGSG-2	SNGSG-2	NYLON (RMS-21)	.172 (4.4)	.031 (0.8)	.109 (2.8)	.037-.071 (0.9-1.8)	.048 (1.2)
NGSG-2.5	SNGSG-2.5		.188 (4.8)	.047 (1.2)	.156 (4.0)	.072-.105 (1.8-2.7)	.060 (1.5)
NGSG-3	SNGSG-3		.106-.164 (2.7-4.2)	.106 (2.7)			
PGSG-2	SPGSG-2	POLYETHYLENE (RMS-06)	.172 (4.4)	.031 (0.8)	.109 (2.8)	.037-.071 (0.9-1.8)	.048 (1.2)
PGSG-2.5	SPGSG-2.5		.188 (4.8)	.047 (1.2)	.156 (4.0)	.072-.105 (1.8-2.7)	.060 (1.5)
PGSG-3	SPGSG-3		.106-.164 (2.7-4.2)	.106 (2.7)			
*PGSG-6	*SPGSG-6		.160 (4.1)	.025 (0.6)	.060 (1.5)	.037-.071 (0.9-1.8)	.048 (1.2)
*PGSG-7	*SPGSG-7		.188 (4.8)	.035 (0.9)	.100 (2.5)	.072-.105 (1.8-2.7)	.060 (1.5)
*PGSG-8	*SPGSG-8		.188 (4.8)	.035 (0.9)	.156 (4.0)	.106 -.164 (2.7-4.2)	.106 (2.7)

*P/N: ...-6 & ...-7 & ...-8 EXTRA FLEXIBLE

PRESSURE-SENSITIVE
ADHESIVE (RMS-96)



SERRATED GROMMETS ONLY

NOTES:

- COLOR: NATURAL OR BLACK;
ADD SUFFIX "B" FOR BLACK
- LENGTH: 100 FT. (3048 cm)

H	SEE ECN #899	SM 01.03.05						
G	RMS-06 WAS RMS-13	DM 12.04.01						
F	REVISED GAP FOR ALL-2 AND -6 SIZES	DLC 9/17/01	TITLE:	GROMMET STRIP W/ADHESIVE			DWG IN	PRELIMINARY
E	REVISED .015/.060 (.4)/(1.5) WAS .015/.055	DLC 7/31/01		FILE #	NGSG	DWN: MO	APP:	
D	DIM. .109 WAS .106	SM 07.24.01	TOLERANCES	MAT'L:	SEE NOTES	DT: 1/4/99	DT:	PART #
C	P/N: ...-8 ADDED	DLC 6/14/01	UNLESS NOTED	RE:	RICHCO, INC.	RICHCO INC.		
B	P/N: ...-6 (...-7) WAS ...-4 (...-5) AND CORRECTED DIMENSIONS	SM 04.30.01	.XX=±.020 .XXX=±.015	PO BOX 804238, CHICAGO, 60680		(773) 539-4060		PRINT TYPE CA
A	ADDED P/N: (S)PGSG-4 & (S)PGSG-5.	SM 04.16.01	FRAC=±1/32 ANG=±1°			SEE TABLE		
REV	DESCRIPTION	ENGR DATE						