

## APPLIANCE COUPLERS

### Accessories

#### Insulating cover

The terminals of the SCHURTER appliance couplers can be protected against unintentional contact by the use of an insulation cover.

They are made of flexible thermoplastic, black, which has the Oxygen Index Rating of 26. Based on the Oxygen Index Rating, material qualifies for UL 94V-0. The cover can be easily mounted from the rear to the corresponding appliance couplers.



#### Order Numbers

Order Numbers	suitable for
0859.0047	KEA (without KEA-Print) KEB I 6200, 6202, 6205, 6220 6600, 472X
0859.0048	6100, 6102
0859.0072	KEC, KFC
0859.0074	KD, 6145
0859.0075	KEB II, KFB II
0859.0076	KE, KMF, EC11
0859.0077	CD
0859.0108	CE
0859.0109	CG, KG, EF11

#### Cord retaining kits

For protection against loosening or accidental disconnection of the plug connector. Can also be mounted later.

The correct kit type (A-M) for each combination of fixed and free components is shown in the selection chart on page 172. The corresponding Order No. for each kit type is shown in the smaller chart.

Horizontal flanged components are secured to the panel using the kit supplied. Vertical flanged or snap-in components require additional drilling for the cord retaining kit as shown in the diagrams below.

Each cord retaining kit consists of:

- 1 Stainless steel retaining clip
- 2 Nickel plated brass pillars
- 2 Nickel plated brass nuts
- 2 Nickel plated beryllium copper crinkle washers



Cut-aways or countersinks on pillars to face inwards.

Order no	Kit type
4700.0001	A
4700.0002	B
4700.0003	C
4700.0004	D
4700.0005	E
4700.0006	F
4700.0007	G
4700.0008	H
4700.0009	J
4700.0010	K
4700.0011	L
4700.0012	M

