



Metric series T, nylon type, general air tubing is offered in 6 different colors. The T series is available in roll sizes 20m and 100m. The 100-meter rolls are available as standard in black and white only.

Τ





Series TAS is designed for air pressure piping to product or assembly while preventing static electricity. It is made of a conductive nylon + flame resistant nylon material (UL-94 standard, V-0) and is available in black 20m or 100m rolls.



TIA

Inch size nylon tubing, series TIA for general air is available as standard in black or white, 20 meter rolls. Additional colors and roll sizes are available upon request.



TISA

The TISA series is a soft nylon tubing made for general air purposes. TISA is available in inch sizes and comes in a 20m roll as standard and is available in black or white.



TIV

Nylon tubing series TIV is for use in air brake systems on heavy duty vehicles along with instrumentation and secondary air systems. TIV is rated to all applicable industry standards. A variety of tube sizes and colors are available. Type A is available in 1/8", 5/32" and 1/4" sizes (non-reinforced) and type B is available in 3/8", 1/2", 5/8" and 3/4" sizes (reinforced).



TRS

Flame resistant TRS soft nylon tubing (Equivalent to UL-94 Standard V-0), is available in 20 and 100 meter rolls. The TRS series is applicable for general air pressure and water in a spark atmosphere such as spot welding. Available colors include black, white, red, blue and green.



<u>TS</u>


Series TS, for general air pressure, Soft Nylon tubing, is available in 6 different colors and 2 roll sizes. 100 meter rolls available in black and white only.

Nylon Tubing

Series T/TIA



For general pneumatic tubing, Nylon tubing Burst Pressure Characteristics Curve and Operating Pressure



A Precautions

Be sure to read before handling.
Refer to pages 15-18-3 to 4 for Safety
Instructions and Common Precautions
on the products mentioned in this
catalog, and refer to pages 15-1-10 to
11 for Precautions on every series.

⚠ Caution

- Applicable for general industrial water. Please consult with SMC if using other kinds of fluid. Surge pressure must be under the max. operating pressure.
 - If the surge pressure exceeds the maximum operating pressure, it will result in damage to fittings and tubes.
- The value of the max. operating pressure is at a temperature of 20°C. Refer to the burst pressure characteristics curve for other temperatures.

Furthermore, abnormal temperature rises caused by adiabatic compression may result in the burst of the tube.

Model/Specifications


ullet — 20 m roll $\;\square$ — 100 m roll (T1613 is reel.)

	Tubing size													
	Metric size (Series T)								Inch size (Series TIA)					
Model	T0425	T0403	T0604	T0645	T0806	T1075	T1209	T1613	TIA01	TIA05	TIA07	TIA11	TIA13	
Tubing O.D. (mm)	4	4	6	6	8	10	12	16	3.18	4.76	6.35	9.53	12.7	
Tubing I.D. (mm)	2.5	3	4	4.5	6	7.5	9	13	2.18	3.48	4.57	6.99	9.56	
Black (B)	-	•							•	<u> </u>	-	<u> </u>	<u> </u>	
White (W)		•	-	<u></u>	-	-	-	-	-	-	•	-	•	
Red (R)	-	_	•		•	•	•						_	
Blue (BU)	-	+	•		•	•	•						-	
Yellow (Y)	-		•		•	•	•						_	
Green (G)	-		•		•	•	•							
	Nominal size (inch)													
	5/32 "				5/16"				1/8 "	3/16"	1/4 "	3/8 "	1/2 "	
Fluid					·		Air/V	Vater				·		

riuiu	All/Water												
Max. operating pressure (at 20°C)	1.5 MPa												
Burst pressure		Refer to the burst pressure characteristics curve.											
Min. bending radius (mm)	13	25	24	36	48	60	75	100	15	20	30	60	75
Operating temperature	-20 to +60°C (Water: 0 to 40°C) (No freezing)												

How to Order

Nylon 12



Made to Order -

(Please contact SMC for specifications in detail, dimensions, delivery and specifications other than those mentioned above.)

100 m reel

Metric size and Inch size except Ø16: Suffix "-X3" to the end of part number. Ex.) TS0425R-100-X3

Longer length reel

Metric size: Suffix "-X3" to the end of part number. Ex.) TS0425G-500-X3

20 m roll Inch size: Suffix "-X4" to the end of part number. Ex.) TISA01BU-20-X4

Material

Made to Order Availability

Part no.	Length Model	T0425 *	T0604 *	T0806 *	T1075 *	T1209 *	TIA01 *	TIA05 *	TIA07 *	TIA11 *	TIA13 *	Color	
	100 m reel	0	0	0	0	0	0	0	0	0	0	Black, White,	
Х3	150 m reel				0							Red, Blue,	
٨٥	200 m reel			0								Yellow, Green	
	500 m reel	0	0									Tellow, Green	
X4	20 m roll						0	0	0	0	0	Red, Blue, Yellow, Green	