

# VM-15LCD

## 15.1" LCD Color Monitor



Our 15.1" high resolution TFT flat screen LCD monitor offers convenient on screen display controls located on the front panel. It includes controls for brightness, contrast, hue, color, vertical and horizontal positioning, and volume. It features audio with front mounted speakers. An input signal detection provides for easy connection. A 12V DC power supply, A/V cable with RCA connectors & BNC/RCA adapter, are included.

### Specifications

Display Type	15.1" Active Matrix TFT LCD Module
Pixel Pitch	.297(H) x .297(V)mm
Resolution	1024 x 768 75Hz
Display Area	12" x 9"
Viewing Angle (H/V)	120/90
Contrast Ratio	400:1
Brightness	250 Cd/m2
Response Time	15 ms (tr), 25 ms (tf)
Input Interface	Input signal: Analog 0.7V peak to peak/sync: separate SYNC (TTL positive or negative)
Cable	D-Sub 15 pin connector
Power Supply	Power supply 100-240V, 50-60Hz/12V DC 35W Max. in "ON" mode
Power Consumption	Under 3W in power saving mode (100Vac)/Under 5w in power saving mode (240Vac)
Power Management	VESA DPMS
Wall Hanging	VESA 100mm
Angle of Elevation	-3~25
Auto Adjust for Brightness	Yes
OSD Control	Yes
Auto Adjustment	Yes
OSD Language	English, German, French, Italian, Spanish
Dimension	14.5" x 14" x 6.75"
Weight	8.2 lbs.
Certificate	Energy Star, UL/CUL, FCC DOC, TUV/GS, CE, TC099, ICES, BSMI, VCCI

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880