

# VM-1401C

## 14" Color Monitor with Audio



Our high performance 14" color monitor offers 420 lines of resolution. It features one camera input, 1 audio input, a hi/lo impedance switch, up front controls, and a composite video with loop through. The monitor provides crisp, clear images that allow you to observe details even in smaller video inset boxes common on quad and multiplexer displays. It is UL and CSA listed.

### Specifications

#### Resolution

Horizontal	420 lines
Vertical	380 lines
Linearity Horizontal	10% maximum
Linearity Vertical	10%
Front Control	Power switch On/Off rocker switch

Electrical Input Voltage	96~256 Vac, 50Hz/60Hz
Power Consumption	40W
Input Signal	0.5 to 2.0 Vp-p composite video, negative synchronization Y:1.0 Vp-p, C:0.7 VP-p

Input Impedance	75 ohms or high (switchable)
Bandwidth	6 MHz
Video Gain	30 db

#### Operation System

NTSC	525 lines, 60 fields/sec
PAL	625 lines, 50 fields/sec

#### Connections

Video (In/Out)	BNC x 2, S-VHS x 1
Audio (In/Out)	RCA Jack x 2
Audio Input Signal	10~150m Vp-p
Audio Amplifier	1W/8 ohm (Incl. a speaker)
Environmental Operation Temperature	14 to 122°F
Storage Temperature	-4 to 158°F (30-90%RH)
General Construction	Steel cabinet with plastic front panel
Dimensions	12.5"L x 14"W x 12.6"H
Weight (per unit)	20 lbs.
Certifications	UL, CE, CSA FDA, FCC, CUL, TUV

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880