

# VMS-2

## Portable CCTV Installation & Test Monitor In a Soft Light-Weight Carrying Case



The VMS-2 portable test monitor is an installer's dream. The ultra-bright high resolution display makes camera adjustments a snap in even the brightest conditions. The lightweight soft carry case can be worn over the shoulder or around the waist for safe and convenient viewing under all conditions. Included in the case with the monitor is a 1000ma rechargeable battery for extended operation. The VMS-2 includes a battery charger, video cable and other accessories to make your jobs go faster. The built in phone jack even allows you to test and monitor an audio signal if available.

### Specifications

LCD technology	TFT active matrix
Display size	4"
Active area	82.1 x 61.8mm
Color system	NTSC
Synchronization	Horizontal 15,625Hz, Vertical 60Hz
Resolution	480 x 234, 112,320 pixels
Audio level	1V/10K
Charging time	8 hours charging time, 4 hours operating time
Input Video Signal	1.0 Vp-p (sync, negative) termination 75 ohm
Dimensions (Monitor)	6"W x 5.04"H x 3"D
Dimensions (Bag)	7.75" W x 5.1" H x 2.55" D
Weight	2.2 lbs.

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880