8430MPDV20

Phase Failure Relay, Type: MP



Availability Stock Item: This item is normally stocked in our distribution facility.

Technical Characteristics

| Approvals | UL Listed File Number: E42240 CCN NLDX - CSA Certified File Number: LR 60905-174 |
|-----------------------------|--|
| Ampere Rating | 5A |
| Contact Arrangement | DPDT |
| Coil Voltage | 120VAC@60Hz |
| Maximum Voltage Rating | 600VAC |
| Mounting Type | Panel or Track |
| Features | Locking Potentiometer Undervoltage Adjustment and an LED Indicating Really Energized |
| Operating Temperature Range | 23 to 122 Degrees F |
| Туре | MP |
| Type of Pins | Tubular |
| Depth | 4.57 Inches |
| Height | 3.50 Inches |
| Width | 2.20 Inches |
| | |

Shipping and Ordering

| Category | 21122 - Relays, Phase Failure and Undervoltage, Panel Mount |
|-------------------|---|
| Discount Schedule | CP1 |
| GTIN | 00785901017738 |
| Package Quantity | 1 |
| Weight | 1.26 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Υ |
| Country of Origin | US |

document.

Generated: 09/16/2009 11:15:07

