8736SCG8V02H20S

REVERSING STARTER 600VAC 27A NEMA

Technical Characteristics

| Control Source | Separate Control Circuit |
|------------------------------|------------------------------------|
| Ampere Rating | 27A |
| Approvals | NEMA Rated - UL Listed |
| Enclosure Type | General Purpose (Indoor) |
| Enclosure Rating | NEMA 1 |
| Horsepower Rating (3-Phase) | 7.5HP@200/230VAC - 10HP@460/575VAC |
| Maximum Voltage Rating | 600VAC |
| Mounting Type | Surface |
| NEMA Size | 1 |
| Number of Poles | 3-Pole |
| Control Voltage | 120VAC@60Hz - 110VAC@50Hz |
| Overload Type | Motor Logic (Class 20) |
| Phase | 3-Phase |
| Starter Type | Reversing |
| Short Circuit Current Rating | 5000 AIR |
| Terminal Type | Screw |
| Depth | 7.53 Inches |
| Туре | S |
| Width | 11.88 Inches |
| Height | 11.88 Inches |
| Weight | 17 Pounds |
| | |

Shipping and Ordering

| 5 . 1 , , , |
|---|
| CP1 |
| 00785901399698 |
| 1 |
| 25.36 lbs. |
| Factory Item: This item is stocked at a Schneider Electric manufacturing plant. |
| N |
| MX |
| |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

