

**Technical Characteristics**

| | |
|-----------------------------|--|
| Catalog Reference Number | 8910CT9301 |
| Type | DP |
| Height | 3.29 Inches |
| Depth | 2.22 Inches |
| Ampere Rating | 25A |
| Approvals | UL Listed File Number E42240 CCN NLDX; CSA Certified File Number LR25490 Class 321104; CE Marked |
| Horsepower Rating (1-Phase) | 2HP@115VAC - 3HP@230VAC |
| Locked Rotor Amperes | 125A@277/460VAC - 100@575VAC |
| Enclosure Type | Open |
| Maximum Voltage Rating | 600VAC |
| Mounting Type | Panel |
| Number of Poles | 1-Pole |
| Operating Voltage | 24VAC@50/60Hz |
| Phase | 1-Phase |
| Action | Non-Reversing |
| Width | 2.16 Inches |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 21353 - Contactors, Definite Purpose, Single Pole, 25 Amp |
| Discount Schedule | CP1B |
| Article Number | 785901748632 |
| Package Quantity | 12 |
| Weight | 0.51 lbs. |
| Availability Code | Factory Item: This item is stocked at a Schneider Electric manufacturing plant. |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.