8910DPA14V02

Definite Purpose Contactor , Non-Reversing, 20A, 3-Phase, 4-Pole



by Schneider Electric

Technical Characteristics

Catalog Reference Number	8910CT9301
Туре	DPA
Height	4.00 Inches
Depth	3.12 Inches
Ampere Rating	20A
Approvals	UL Listed File Number E42240 CCN NLDX; CSA Certified File Number LR25490 Class 321104; CE Marked
Horsepower Rating (1-Phase)	1HP@115VAC - 2HP@230VAC
Horsepower Rating (3-Phase)	5HP@230VAC - 7.5HP@460/575VAC
Locked Rotor Amperes	120A@230VAC - 100A@460VAC - 90A@575VAC
Enclosure Type	Open
Maximum Voltage Rating	600VAC
Mounting Type	Panel
Number of Poles	4-Pole
Operating Voltage	120VAC@60Hz - 110VAC@50Hz
Phase	3-Phase
Action	Non-Reversing
Width	3.17 Inches

Shipping and Ordering

Category	21341 - Contactors, Definite Purpose, 20 Amp
Discount Schedule	CP1B
Article Number	785901080121
Package Quantity	8
Weight	1.31 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 05/29/2009 11:29:51

