8910DPA34V14

Definite Purpose Contactor , Non-Reversing, 30A, 3-Phase, 4-Pole



by Schneider Electric

Availability Stock Item: This item is normally stocked in our distribution facility.

Technical Characteristics

Depth 3.12 Inches Ampere Rating 30A Approvals UL Listed File Number E42240 CCN NLDX; CSA Certified File Number LR25490 Class 321104; CE Marked Catalog Reference Number 8910CT9301 Horsepower Rating (1-Phase) 2HP@115VAC - 5HP@230VAC Horsepower Rating (3-Phase) 10HP@230VAC - 15HP@460/575VAC Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Туре	DPA
Ampere Rating 30A Approvals UL Listed File Number E42240 CCN NLDX; CSA Certified File Number LR25490 Class 321104; CE Marked Catalog Reference Number 8910CT9301 Horsepower Rating (1-Phase) 2HP@115VAC - 5HP@230VAC Horsepower Rating (3-Phase) 10HP@230VAC - 15HP@460/575VAC Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Height	4.00 Inches
Approvals UL Listed File Number E42240 CCN NLDX; CSA Certified File Number LR25490 Class 321104; CE Marked Catalog Reference Number 8910CT9301 Horsepower Rating (1-Phase) 2HP@115VAC - 5HP@230VAC Horsepower Rating (3-Phase) 10HP@230VAC - 15HP@460/575VAC Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage Phase 3-Phase	Depth	3.12 Inches
Approvals 321104; CE Marked Catalog Reference Number 8910CT9301 Horsepower Rating (1-Phase) 2HP@115VAC - 5HP@230VAC Horsepower Rating (3-Phase) 10HP@230VAC - 15HP@460/575VAC Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Ampere Rating	30A
Horsepower Rating (1-Phase) 2HP@115VAC - 5HP@230VAC Horsepower Rating (3-Phase) 10HP@230VAC - 15HP@460/575VAC Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Approvals	
Horsepower Rating (3-Phase) Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles Operating Voltage 24VAC@50/60Hz Phase	Catalog Reference Number	8910CT9301
Locked Rotor Amperes 180A@230VAC - 150A@460VAC - 120A@575VAC Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Horsepower Rating (1-Phase)	2HP@115VAC - 5HP@230VAC
Enclosure Type Open Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Horsepower Rating (3-Phase)	10HP@230VAC - 15HP@460/575VAC
Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Locked Rotor Amperes	180A@230VAC - 150A@460VAC - 120A@575VAC
Mounting Type Panel Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Enclosure Type	Open
Number of Poles 4-Pole Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Maximum Voltage Rating	600VAC
Operating Voltage 24VAC@50/60Hz Phase 3-Phase	Mounting Type	Panel
Phase 3-Phase	Number of Poles	4-Pole
	Operating Voltage	24VAC@50/60Hz
Action Non-Reversing	Phase	3-Phase
	Action	Non-Reversing
Width 3.17 Inches	Width	3.17 Inches

Shipping and Ordering

Category	21343 - Contactors, Definite Purpose, 30 Amp
Discount Schedule	CP1B
Article Number	785901073512
Package Quantity	8
Weight	1.31 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ

document.

Generated: 06/03/2009 17:31:12

