Product Data Sheet

8910DPA73V14

Definite Purpose Contactor , Non-Reversing, 75A, 3-Phase, 3-Pole



by Schneider Electric	

Technical Characteristics

Enclosure Type	Open
Ampere Rating	75A
Approvals	UL Listed - CSA Certified - CE Marked
Horsepower Rating (1-Phase)	5HP@115VAC - 15HP@230VAC
Maximum Voltage Rating	600VAC
Mounting Type	Panel
Number of Poles	3-Pole
Locked Rotor Amperes	450A@230VAC - 375A@460VAC - 300A@575VAC
Horsepower Rating (3-Phase)	25HP@230VAC - 40HP@460/575VAC
Operating Voltage	24VAC@50/60Hz
Phase	3-Phase
Action	Non-Reversing
Туре	DPA
Depth	4.37 Inches
Height	5.20 Inches
Width	3.39 Inches

Shipping and Ordering

Category	21347 - Contactors, Definite Purpose, 75 Amp
Discount Schedule	CP1B
GTIN	00785901118350
Package Quantity	1
Weight	3.68 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

document.

Generated: 11/23/2009 15:47:17

